



AGICO

Anyang General International Co.,Ltd

Synopsis

GT series peanut peeler is form decorticating equipment, machine helves, Air Fan and clearing skin equipment three part. The machine adopt to roll and rubbed for separated into two parts kernel and skin, in order to it have steady performance, long time life, high peeling rate, high output rate,very low imperfect kernels, good quality of product, and processing a lot goods by combination several units, it is suitable for processing various types and sizes blanched peanut kernels.

Technical parameters

- Imperfect kernels: 8%
- Peeling rate: 96%
- Voltage: 380V/220V
- Frequency: 50hz

Model		GT-4	GT-8	GT-12
Capacity (kg/h)		200-250	400-450	600-650
Powder (kw)	main machine	0.37	0.74	1.1
	assistant machine	0.37	1.1	1.5

Note: Different capacity peeler can accord to buyer's demand.

Installation

Leveling machine off and fixation, fitting storage bag or chest on the exit of air fan.

Notice proceeding and process of Operation

Firstly, checking electrocircuit connection and machine part in order to confirming all is ok, then put on machine to check whether running in gear.

1. Putting on air fan.
2. Rightly circumgyrateing handle of operation discharge flitch, let operation discharge flitch to go up in order to limit the material out velocity of Flow.
3. startup peeler.
4. Adjust operation discharge flitch in order to imperfect rate is lowest and peeling rate is highest, all is ok.

Requirement of material

1. The moisture of dryed material is about 4%
2. The temperature of material is normal temperature
3. No stone etc. impurity in avoid to mangle roller.

Address: Suite A, 4/F, Jinhao Business Bld., Renmin Rd. Anyang, Henan, China
Tel: 86-372-5953961 ext 8005 Fax: 86-372-5951936
Email: info@chinesepeanut.com Website: <http://www.chinesepeanut.com>